
SES-160-II-53FC-i, BOTTLE LABELLING UNIT



THE REQUEST:

Front, back and all-round labelling in various different formats

THE CHALLENGE:

Products from 50 ml to 10 l featuring various label sizes, two-way-switching between side and wraparound labelling, label chain presence detection by means of vision sensors, application of labels with UDI-compliant imprint and inspection of contents via camera system, automatic rejection of products with missing or illegible print, combination of the individual assemblies in a small space

OUR SOLUTION:

Multifunctional system with very short set-up times thanks to scales, format tables and recipe management

AT A GLANCE:

Technical Data	SES-160-II-53FC-i
General Data	
Output	In-Line, 30–60 pcs./min
Installed labelling machines	SES-160-II left hand mounted, SES-160-II-53FC-i right hand mounted
Execution	With built-in camera system for UDI detection and data processing
Weights and measures	
Speed	12 m/min
min. label width	25 mm
max. label width	160 mm
Label length	10 mm ÷ 180 mm (optional 300 mm)
Diameter of labelreel	max. Ø 300 mm
Dispensing speed	max. 40 m/min
Weight of the unit	approx. 1000 kg
Electrical Data	
Control System	SPS-control, graphic display (colour) for operating and malfunction indication
Connected load	max. 6 kVA
Voltage/Freq.	400 V AC/50 Hz
Label detection	photocell
Product detection	photocell



SEIT 1984 IHR PARTNER FÜR ETIKETTIERLÖSUNGEN

CONTACT:

SES Straßburg-Etikettier-Service GmbH, Zunftstrasse 13, 21244 Buchholz i.d.N. Phone: +49 4181 7044, Email: info@ses-strassburg.de, www.ses-strassburg.de